

K6-F14-J4125

Intel Celeron J4125



Parameter list

CPU	Intel Celeron J4125 2.0 GHz - 2.7GHz
Cores/Threads	4 Cores / 4 Threads
Cache	4 MB Cache
TDP	10W
Architecture	Products formerly Gemini Lake Refresh
Memory	2*DDR4L slot,support 32G max
Storage	SSD (M.2 SATA)
	Optional HDD (supports expansion of a 2.5-inch hard drive)
Audio Card	HD Audio realtek ALC 662
Graphics	Intel® UHD Graphics 600
Network	10/100/1000Mbps adaptive RTL 8111E
Extendable	WIFI+BT Module (M.2 PCIE), support 4G module with available sim slot
OS Support	Windows (Not include XP) & Linux
I/O Ports	4*USB3.0、2*USB2.0、1*DP、2*HDMI、2*RJ45、1*DC、1*MIC-IN、1*LINE-OUT、1*TYPE-C、1*CLS、

BIOS Function

Display Mode	4K/ 3 displays （support copy mode,extended mode）	
	Max Resolution(DP): 4096x2160@60Hz; Max Resolution(HDMI): 4096*2160@30Hz	
Boot Mode	PXE / Auto-power-on / Wake-on-LAN	
Intel Virtualization	Support VT-x, VT-d	
Intel Hyper-Threading	Support	
Working Environment	Temperature: -10~60 °C	Relative Humidity: 0~95% (No Condensation)
Working Voltage	DC 12V - 3 A	
Static Electricity	Contact discharge 2K, Air discharge 6K	
Storage Environment	Temperature: -10~60 °C	Relative Humidity: 0~95% (No Condensation)

K6-F14-J4125

Intel Celeron J4125



					I/O Port				
01	POWER ON/OFF		02	USB3.0*4		03	RESET		
04	Type-C		05	MIC		06	SPK		
07	Indicator light		08	USB2.0*2		09	RJ45 Gigabit LAN		
10	RJ45 Gigabit LAN		11	DP		12	HDMI		
13	HDMI		14	DC12V Input		15	/		
16	Ground hole		17	Lock slot					
Size	L 133.8mm*W 126.6mm*H 47mm					Weight	Net : 1.0kg		Gross : 1.8kg

Specification

Features	Adopt a plastic top cover with aluminum alloy body design; this top cover uses brushed texture with high gloss mirror effect.		
Heat Dissipation	with FAN		
Bracket	Dedicated bracket; Support VESA bracket		
Packing Box	Kraft paper color box + Anti-fall corrugated outer box		
Packing List	Power Adapter * 1	Power Cable * 1	Bracket * 1
	User Manual * 1	QA Card * 1	Screws * 1