

# 1 Mini PC K8-F17HI

## Intel Pentium 3710



<b>CPU</b>	Intel Pentium 3710 1.6GHz~2.56GHz	
<b>Cores/Threads</b>	4 Cores / 4 Threads	
<b>Cache</b>	2 MB L2 Cache	
<b>TDP</b>	6W	
<b>Architecture</b>	Braswell	
<b>Memory</b>	1*SO-DIMM DDR3 slot	
<b>Storage</b>	SSD (mSATA) Optional HDD (supports expansion of a 2.5-inch hard drive)	
<b>Audio Card</b>	HD Audio ALC897	
<b>Graphics</b>	Intel HD Graphics	
<b>Network</b>	10/100/1000Mbps Adaptive, RTL 8111H / RTL8111GUS	
<b>Extendable</b>	WIFI+Bluetooth Module (M.2 PCIE)	
<b>OS Support</b>	Windows 10/ Windows 11/Linux	
<b>I/O Ports</b>	4*Serial RS232/RS485 COM, 1*HDMI, 1*VGA, 2*USB3.0, 2*USB2.0, 2* RJ45, 1*RJ11, 1*PS2, 1*MIC & SPK, 1*DC_IN (Phoenix Connector)	
<b>Internal I/O Ports</b>	4*COM 、 1*F-PANEL 、 1*PCIE GPIO 、 1*CPU-FAN、 1*TPM Pin、 1*SATA HDD (SATA III) 1* LVDS、 1*SPEAKER(4pin)、 1*SIM、 1*CMOS、 AT_MODE(AUTO_PWR) 、 1*6pin 、 1*USB2.0	
	<b>BIOS Function</b>	
<b>Display Mode</b>	Dual Display(HDMI+VGA) Max Resolution(VGA): 1920*1080; Max Resolution(HDMI): 3840*2160	
<b>Boot Mode</b>	UEFI PXE / Auto-power-on / Wake-on-LAN / WDT / AMI 64M BIOS / Timed startup / Dynamic time startup	
<b>Intel Virtualization</b>	Support VT-x,VT-d	
<b>Intel Hyper-Threading</b>	Support	
<b>Working Environment</b>	Temperature: -10~65 °C	Relative Humidity: 0~95% (No Condensation)
<b>Working Voltage</b>	DC 12V - 5A	
<b>Static Electricity</b>	Contact discharge 2K, Air discharge 6K	
<b>Storage Environment</b>	Temperature: -10~60 °C	Relative Humidity: 0~95% (No Condensation)

## 2 Mini PC K8-F17HI

Intel Pentium 3710



01	PS2	02	RJ11	03	RS232 COM*4
04	MIC & SPK	05	USB2.0*4	06	RJ45 Gigabit LAN
07	USB3.0*2	08	HDMI	09	Indicator Light
10	VGA	11	DC_IN (Phoenix Connector)		
<b>Size</b>	L 197.4mm*W 126.3mm*H 47.5mm			<b>Weight</b>	Net : 1.2kg    Gross : 1.8kg

### Specification

**Features** Use aluminum alloy shell, industrial style, heavy and solid, unique appearance design

**Heat Dissipation** Fanless Passive Cooling

**Bracket** Dedicated bracket; Support VESA bracket

**Packing Box** Kraft paper color box + Anti-fall corrugated outer box

**Packing List**

Power Adapter * 1	Power Cable * 1	Bracket * 1
User Manual * 1	QA Card * 1	Screws * 1