

K7-F14-5600U/5500U

Intel Core i7 5600U/ i7 5500U



CPU	Core i7 5600U 2.6GHz-3.2GHz / Core i7 5500U 2.4GHz-3.0GHz	
Cores/Threads	2 Cores / 4 Threads	
Cache	4 MB Cache	
TDP	15W	
Architecture	Broadwell	
Memory	2*DDR3L slot, max support 16GB	
Storage	SSD (mSATA) Optional HDD (supports expansion of a 2.5-inch hard drive)	
Audio Card	HD Audio realtek ALC 662	
Graphics	Intel HD Graphics 5500	
Network	10/100/1000Mbps Adaptive, RTL 8111E	
Extendable	WIFI+Bluetooth Module(M.2 PCIE)	
OS Support	Windows (Not include XP) & Linux	
I/O Ports	4*USB3.0、 2*USB2.0、 1*VGA、 2*HDMI、 2*RJ45、 1*DC、 1*MIC-IN、 1*LINE-OUT、 1*TYPE-C、 1*CLS	
Internal I/O Ports	2~4*COM-1 Pin、 1*CPU-FAN、 1*JP1 Pin、 1*FP AUDIO Pin、 1*JP3 Pin、 1*TPM Pin、 1*PCIE-GPIO Pin、 1*BAT_CON(Battery)、 1*Power Switch indicator Pin	

Display Mode	4K/ Support Triple display (Duplicate mode, Extend mode) Max Resolution(VGA): 1920*1080@60Hz; Max Resolution(HDMI): 3840*2160@30Hz;	
Boot Mode	PXE / Auto-power-on / Wake-on-LAN	
Intel Virtualization	Support VT-x, VT-d	
Intel Hyper-Threading	Support	
Working Environment	Temperature: -10~60 °C	Relative Humidity: 0~95% (No Condensation)
Working Voltage	DC 12V - 5A	
Static Electricity	Contact discharge 2K, Air discharge 6K	
Storage Environment	Temperature: -10~60 °C	Relative Humidity: 0~95% (No Condensation)

K7-F14-5600U/5500U

Intel Core i7 5600U/ i7 5500U



01	POWER ON/OFF	02	USB3.0*4	03	RESET
04	Type-C	05	MIC	06	SPK
07	USB2.0*2	08	RJ45 Gigabit LAN	09	RJ45 Gigabit LAN
10	VGA	11	HDMI	12	HDMI
13	DC12V Input				
Size	L 133.8mm*W 126.6mm*H 47mm			Weight	Net : 0.65kg Gross : 1.4kg

Specification

Features	Adopt a plastic top cover with aluminum alloy body design; this top cover uses brushed texture with high gloss mirror effect.		
Heat Dissipation	with FAN		
Bracket	Dedicated bracket; Support VESA bracket		
Packing Box	Kraft paper color box + Anti-fall corrugated outer box		
Packing List	Power Adapter * 1	Power Cable * 1	Bracket * 1
	User Manual * 1	QC Card * 1	Screws * 1