

1 Mini PC K8-F17HI-N3710

Intel Pentium N3710



CPU	Intel Pentium N3710 1.6GHz~2.56GHz	
Cores/Threads	4 Cores / 4 Threads	
Cache	2 MB L2 Cache	
TDP	6W	
Architecture	Braswell	
Memory	1*SO-DIMM DDR3 slot	
Storage	SSD (M.2 SATA) Optional HDD (supports expansion of a 2.5-inch hard drive)	
Audio Card	HD Audio ALC897	
Graphics	Intel HD Graphics	
Network	10/100/1000Mbps Adaptive, RTL 8111H / RTL8111GUS	
Extendable	WIFI+Bluetooth Module (M.2 PCIE)	
OS Support	Windows 10/ Windows 11/Linux	
I/O Ports	4*Serial RS232/RS485 COM, 1*HDMI, 1*VGA, 2*USB3.0, 4 *USB2.0, 1 * RJ45, 1*RJ11, 1*PS/2, 1*MIC&SPK, 1*DC IN (Phoenix Connector)	
Internal I/O Ports	4*COM 、 1*F-PANEL 、 1*PCIE GPIO 、 1*CPU-FAN、 1*TPM Pin、 1*SATA HDD (SATA III) 1* LVDS、 1*SPEAKER(4pin)、 1*SIM、 1*CMOS、 AT_MODE(AUTO_PWR) 、 1*6pin 、 1*USB2.0	
		BIOS Function
Display Mode	Dual Display(HDMI+VGA) Max Resolution(VGA): 1920*1080; Max Resolution(HDMI): 3840*2160	
Boot Mode	UEFI PXE / Auto-power-on / Wake-on-LAN / WDT / AMI 64M BIOS / Timed startup	
Intel Virtualization	Support VT-x,VT-d	
Intel Hyper-Threading	Support	
Working Environment	Temperature: -10~65 °C	Relative Humidity: 0~95% (No Condensation)
Working Voltage	DC 12V - 3 A	
Static Electricity	Contact discharge 2K, Air discharge 6K	
Storage Environment	Temperature: -10~60 °C	Relative Humidity: 0~95% (No Condensation)

2 Mini PC K8-F17HI-N3710

Intel Pentium N3710



01	PS/2	02	RJ11	03	RS232 / RS485 COM*4
04	MIC & SPK	05	USB2.0*4	06	RJ45 Gigabit LAN
07	USB3.0*2	08	HDMI	09	Indicator Light
10	VGA	11	DC_IN (Phoenix Connector)		
Size	L 197.4mm*W 126.3mm*H 47.5mm			Weight	Net : 1.2kg Gross : 1.8kg

Specification

Features Use aluminum alloy shell, industrial style, heavy and solid, unique appearance design

Heat Dissipation Fanless Passive Cooling

Bracket Dedicated bracket; Support VESA bracket

Packing Box Kraft paper color box + Anti-fall corrugated outer box

Packing List

Power Adapter * 1	Power Cable * 1	Bracket * 1
User Manual * 1	QA Card * 1	Screws * 1