

MINI PC K6-F13G

Intel Celeron N2840



CPU	Intel Celeron N2840 2.16 GHz
Cores/Threads	2 Cores / 2 Threads
Cache	1 MB L2 Cache
TDP	7.5W
Architecture	Bay Trail
Memory	1*DDR3L slot, max support 8GB
Storage	SSD (mSATA)
	Optional HDD (the motherboard supports the expansion of a 2.5-inch hard drive) The shell does not support HDD expansion
Audio Card	HD Audio realtek ALC 662
Graphics	Intel HD Graphics
Network	10/100/1000Mbps Adaptive, RTL 8111F
Extendable	WIFI+Bluetooth Module (M.2 PCIE)
OS Support	Windows (Not include XP) & Linux
I/O Ports	5*USB2.0, 1*USB3.0, HDMI, VGA, 1*RJ45, 1*COM, 1*SIM slot, 1*TF slot, 1*DC, 1*MIC-IN, 1*LINE-OUT
Internal I/O Ports	1*FP, 1*JP3, 2~4*COM, 1*GPIO

BIOS Function

Display Mode	1080P/ Support Dual display (Duplicate mode, Extend mode)
	Max Resolution(VGA): 1920*1080@60Hz; Max Resolution(HDMI): 1920*1080@60Hz
Boot Mode	PXE / Auto-power-on / Wake-on-LAN
Intel Virtualization	Support VT-x, Not support VT-d
Intel Hyper-Threading	Not support
Working Environment	Temperature: -10~60 °C Relative Humidity: 0~95% (No Condensation)
Working Voltage	DC 12V - 3A
Static Electricity	Contact discharge 2K, Air discharge 6K
Storage Environment	Temperature: -10~60 °C Relative Humidity: 0~95% (No Condensation)

MINI PC K6-F13G

Intel Celeron N2840



01	DC 12V input	02	HDMI	03	VGA
04	RJ45 Gigabit LAN	05	USB2.0*2	06	RJ45 COM
07	Power on/off	08	SIM slot	09	TF slot
10	USB2.0*3	11	USB3.0*1	12	MIC & SPK
Size	L 133.8mm*W 126.6mm*H 36.5mm			Weight	Net : 0.6kg Gross : 1.3kg

Features	Using aluminum alloy shell, unique ice fin appearance design, fanless and more quiet		
Heat Dissipation	Fanless Passive Cooling		
Bracket	Dedicated bracket; Support VESA bracket		
Packing Box	Kraft paper color box + Anti-fall corrugated outer box		
Packing List	Power Adapter * 1	Power Cable* 1	VESA Bracket * 1
	User Manual * 1	QC Card * 1	Screws * 1

Overall Performance Mark	Master Lu 5.20		CINBENCH R20	3D MARK11	PC MARK 10
	CPU	GPU			
	12240	2324	156	P239	1393
Video Experience					
Game Experience					
Office Experience					